



Group S check list for MG manufactured vehicles.

Vehicle Number Date Vehicle complies Yes / No

Logbook Number x/√

MG 4 Cylinder MGB's and Midgets from 1961-1980 Body work original

Front Suspension: Original type with allowed modifications Max 3° Negative

Rear Suspension: Original type with allowed modifications

Brake Front Discs Thickness: MGB 273.4 x 8.8 mm Midget 209.8 x 7.5 mm

Brake Caliper: original Lockheed

Brake master Cylinder: Complies.

Note: Booster servo maybe fitted to car log booked SC 1974 on

Brake Rear Drum, Original size

Engine sealed: Yes / No Engine Seal number:

Engine seal document sighted: Engine number:

Cooling System Complies:

Carburetor: (MGB) 1 x45 DCOE Weber or 2 x SU HS2 (Midget) 2 x SU HS4

Fuel Tank: complies

Transmission: BMC as fitted to MGB and Midget.

Final Drive BMC Banjo or Salisbury as fitted to MGB and Midget.

Electrical system: Wiring harness must be original with accessories working.

Wheels and tyres

MGB Wheels: Disc or Wire 14" max width 6

Tyres: 14" x 185 with a minimum aspect ratio of 60%.

Note: MGB GT can run 14 x 195 refer M/Sport Aust. Tyre list group S.

Midget Wheels: Disc or Wire 13" max width 5"

Tyres: 13" x 175 with a minimum aspect ratio of 60%, refer M/Sport Aust. group S Tyre list.

List of excepted modification's

1.

2.

Note: Photos of the Car, Engine number and Engine seal tag with number showing are to be attached to this sheet.

Inspectors:

Names: Signed:

Names: Signed: